

B-TAPE

BUTYL FLANGE GASKET TAPE



FEATURES

- *Excellent cold temperature adhesion*
- *Formulated for all weather use*
- *Exceeds all flange manufacturers' requirements*
- *Permanently flexible, never hardens*
- *Seals low, medium, and high pressure flanged HVAC duct systems*

TECHNICAL SPECIFICATIONS	
Packaging	20 - 3/16" x 5/8" x 25 ft./roll, rolls per case per case
Shelf Life	Twenty years minimum
Pressure Rating	Maximum 16" water column pressure rating
Solids Content	100%
Color	Gray
Weathering	Passes 1000 hrs, Weather-o-meter (ASTM D750)
Temperature Limits	Storage and application... 20°F to 110°F Service..... -40°F to 190°F
Class 1 Smoke and Flame Rating	UNDERWRITERS LABORATORIES INC. GENERAL USE TAPES Applied to Organic, Reinforced Cement Board. Flame Spread5 Smoke Developed0 IKF9 Tested in accordance with UL 723, and ASTM E-84. Satisfies the requirements of NFPA 90A, 90B, and 225.

DESCRIPTION

B-TAPE is a permanently flexible, soft gum tape that is suitable for indoor and outdoor applications. It will not harden, crack, chalk, or cold flow when exposed to high temperatures. It also has excellent cold temperature adhesion.

RECOMMENDED USES

Use **B-TAPE** to seal all types of HVAC flanged duct systems that require a gasketing material or any application where a weather resistant, flexible sealing gum is required.

APPLICATION INSTRUCTIONS

Cut tape to desired length and peel off liner. Press onto flange face that is free from oil, grease, dirt and water. Make up flange according to manufacturers instructions.

SPECIFICATION APPROVALS

MIL-C-18969B, Type II, Class B; TT-C-1796A, Type II, Class B (supercedes MIL-C-18909B); Meets USDA requirement for use in meat and poultry processing areas under Federal inspection.

CLEAN UP

Use warm water and soap.

Polymer Adhesives Sealant Systems Inc., is proud to be affiliated with the following organizations:



CLASSIFIED
IKF9



Norte 94, #4534 Nueva Tenochtitlan
07890 Gustavo A. Madero, CDMX

✉ info@solucionesenaislamiento.com

☎ (55) 9129-8722 📞 (55) 7990-6920

● www.solucionesenaislamiento.com