

PREMIUM PERFORMANCE DOUBLE-COATED POLYESTER FILM TAPE

TYPICAL APPLICATIONS

- Suited for mounting banners, light signs, window blinds, emblems and nameplates
- Also used where long-term or permanent bonding/attachment is required, including POP displays and laminating materials

ADVANTAGES AND BENEFITS

- Excellent adhesion and shear
- Excellent conformability to most irregular surfaces
- Superior moisture resistance in high humidity environments
- Outstanding mounting and laminating system for foams, foils and nameplates
- Converter friendly

CONSTRUCTION

Overall Grade/Function: General Purpose
Backing: 0.5 mil (12 micron) polyester film
Adhesive: Solvent acrylic
Liner: White poly-coated kraft



COLOR(S)

Clear (CLR)

STANDARD WIDTH(S)

24 mm 48 mm 72 mm 1040 mm

STANDARD LENGTH(S)

50 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	15.5 lbs/in width	27 N/10 mm
Adhesion to Stainless Steel	60 oz/in width	6.5 N/10 mm
Thickness (with liner)	8.6 mils	0.22 mm
Thickness (without liner)	4.2 mils	0.11 mm
Elongation	110%	110%
Maximum Service Temperature	257 F	125 C


Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.



Distribuidores Autorizados


Norte 94, #4534 Nueva Tenochtitlan
07890 Gustavo A. Madero, CDMX

✉ info@solucionesenaislamiento.com

☎ (55) 9129-8722 📞 (55) 7990-6920

● www.solucionesenaislamiento.com