

# CT-DT 3520 S


## CINTA PARA DUCTO ALTA RESISTENCIA GRIS / NEGRA

### CARACTERISTICAS:

- Adhesivo de goma agresivo
- Fuerte, flexible y duradera
- Se adapta a superficies irregulares
- Funciona en condiciones calidas y frias

### APLICACIONES:

- Sellado de juntas, reparación y enmascaramiento interior y exterior
- De uso general y empaque



Construction	 <b>Tela de poliester tejida recubierta</b> <b>Adhesivo de goma</b>	
PROPIEDADES	Metrica	Engles
Espesor	70+/-1 mesh (35x35 counts/pulgadas)	70+/-1 mesh (35x35 counts/pulgadas)
Espesor total	0.23 mm	9.1 mil
Adhesión al acero	7.5 N / cm 0.76 Kg/cm	68 Oz/pulgadas
Rollo Base (11 mm ball)	12 cm	4.72 pulgadas
Resistencia a la tracción	35 N / cm	20 Lb/pulgadas
Temperatura de servicio	-20 +60 C	- 4 + 140° F
Core I.D.	76mm	3"
Color	Gris /Negro // otros colores disponibles bajo pedido	
Ancho de rollo	48mm (2"), 50mm; 60mm, 72 mm (3"), 75mm; 100mm (4")	
Largo de rollo	27m (30 yards), 30m (100'), 45m (50 yards), 50m (55 yards); 55m, 100m	

- The data above are typical results from tests conducted on samples taken from production runs and may be updated without notice. Typical values are not intended to be used for specification development. Tolerance: Weight and thickness: 10%; width: 3mm; length: Cut Roll: 0.3m, Jumbo Roll 0.5%.
- The product should be stored in the original packaging material at 20 +/- 5 C and 40-60% relative humidity and protected from direct sunlight, heat and moisture. Shelf life: One year when stored at the conditions described above.
- The surface to which the tape is applied must be clean, dry, free of grease and oil and other contaminants and deposits. Recommended temperature of application: 50 - 105 °F (10 - 40 °C).
- The user is ultimately responsible for determining whether the product is fit for a particular surface and suitable for user's application. No claims will be accepted after product is installed. The user should make necessary tests and trial-application of the tape to confirm suitability for user's special purpose and method of application.
- Self adhesive tapes are designed for sealing applications only. In the instance when the sides of the joint are subject to mechanical stress, both sides should be securely positioned using appropriate fasteners or hangers prior to the self adhesive tapes application.
- Calem Technology warranty that the product is free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment, Calem Technology shall, upon notification thereof and substantiation that the product have been stored and applied in accordance with the above requirements, at Calem Technology discretion, replace or credit the product's purchasing price equivalent.
- Limitation of liability. Calem Technology Inc. and seller of CT Tape products will not be liable for any loss or damage arising from the CT Tape product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



1-604-277-6643  
186-8120 No. 2 Road  
Richmond, BC  
V7E 3E6, Canada

Feb 2016



Distribuidores Autorizados

Norte 94, #4534 Nueva Tenochtitlan  
07890 Gustavo A. Madero, CDMX

✉ info@solucionesenaislamiento.com

☎ (55) 9129-8722 ☎ (55) 7990-6920

● www.solucionesenaislamiento.com